



AC/DC Kilovoltmeters and Dividers


TESTING APPLICATIONS

- Units can be used for calibrations and voltage monitoring of high voltage systems
- Traceable calibration to NIST, USA
- Voltage divider can also be used with other measuring devices such as an oscilloscope.

- Precision accuracy and lasting reliability
- Compactly packaged in rugged carrying case for field or laboratory use
- Battery or line powered
- 100 kV and 200 kV models standard, higher voltages are available upon request

DESIGN FEATURES

- Units include a high voltage divider, metering section, and interconnect cables which are stored in a compact, durable case
- Line power indicator lamp
- Low battery indicator lamp
- 4½ digit LCD display with adjustable backlight
- Low and High range voltage selector
- Cables, 25 ft (8 m)





VOLTAGE MEASUREMENT FUNCTIONS

PEAK /√ 2	Peak responding	
PEAK	Peak value of voltage	
RMS	True RMS value	
AVERAGE AC/DC	True average value, 0.637 of peak value for pure sine wave signal (not calibrated to RMS equivalent)	
PEAK DC	Peak value of DC including peak of ripple	
RMS RIPPLE	RMS value of ripple voltage on DC	
Accuracy	1% of reading from 10-100% of range	
Frequency Response (Sinusoidal Waveform)	PEAK /√ 2	DC, 5-1000 Hz
	RMS	20-1000 Hz
	RMS RIPPLE	20-1000 Hz
	AVERAGE	DC, 20-1000 Hz

	MODEL	KVM100	KVM200
SPECIFICATIONS	INPUT POWER	100-240 VAC, 0.4 A, 47-63 Hz, Single Phase	
	BATTERY POWER	9.6 V, Ni-MH, 3200 mA hr	
	INPUT CHARGING JACK	+18 VDC, .8 A	
	RESOLUTION	RANGE	RANGE
	1 VOLT	0-20 kV	0-20 kV
	10 VOLT	0-100 kV	0-200 kV
	HIGH VOLTAGE INPUT		
	LOW RANGE	0-20 kV AC/DC	0-20 kV AC/DC
	HIGH RANGE	0-100 kV AC/DC	0-200 kV AC/DC
	PEAK	0-142 kV AC	0-200 kV AC
DIVIDER IMPEDANCE	RESISTANCE	380 M Ohms	760 M Ohms
	CAPACITANCE	≤200 pF	≤100 pF
	RATIO	10,000:1	10,000:1
DIMENSIONS & WEIGHT	Length	9 1/2" (241 mm)	9 1/2" (241 mm)
	Width	9 1/2" (241 mm)	9 1/2" (241 mm)
	Height	30 1/2" (775 mm)	43 1/2" (1105 mm)
	Weight	30 lbs (14 kgs)	43 lbs (20 kgs)
SHIPPING SIZE	Length	14" (356 mm)	14" (356 mm)
	Width	14" (356 mm)	14" (356 mm)
	Height	36" (914 mm)	50" (1270 mm)
	Weight	36 lbs (16 kgs)	50 lbs (23 kgs)

OPTIONS

DVD100, 100 kV AC/DC Divider 10,000:1 ratio
 DVD200, 200 kV AC/DC Divider 10,000:1 ratio
 KVM Metering Head, requires 10,000:1 ratio Divider

ENVIRONMENTAL CONDITIONS

10-40°C, indoor/outdoor in fair weather
 Humidity <95%, non-condensing
 Altitude <3000 ft (1000 meters)

High Voltage • High Current • High Power Test Systems and Components

ISO 9001
 CERTIFIED



www.phenixtech.com

World Headquarters
 Phenix Technologies, Inc.
 75 Speicher Drive
 Accident, MD 21520 USA
 Ph: +1.301.746.8118
 Fx: +1.301.895.5570
 Info@phenixtech.com

Branch Offices

Phenix Systems AG
 Riehenstrasse 62A, 4058 Basel, Switzerland
 Ph: +41.61.383.2770 • Fx: +41.61.383.2771
 Info@phenixsystems.com

Phenix Asia
 Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan
 Ph: +886.2.2835.9738 • Fx: +886.2.2835.9879
 Info@phenixasia.com

